

**PBS-M / PBS-F**

**For combined walls (Peiner-type beams) with PZ/PZC (ball & socket) sheet piles**

**Installation**

1. Install the Peiner Beams first.
2. Lay the sheet piling horizontally and thread the connector into the interlock of the sheet piling, adjusting the connector to the appropriate position (please review the proper interlocking examples, as shown to the right). This can be done at the mill, at a distributor's yard, or on the job site (go here: [www.PilePro.com/thread](http://www.PilePro.com/thread)).
3. Tack or spot-weld the connector in place. Typically, a ~250mm (~10") weld, attaching the connector to the sheet pile to the top is sufficient.
4. Grasp the sheet pile (with connectors already attached) and thread between the already installed Peiner type beams.
5. Lower/drive the sheet piling to the level of the Peiner type beam.

**Properties**

Steel grade:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Weight PBS-M:	~ 9 lb / ft
Weight PBS-F:	~10.66 lb / ft

**PBS-M / PBS-F****Raccord pour rideaux mixtes**

Pour PZ et PZC (Ball + Socket)

**Domaines d'emploi**

Rideaux mixtes avec des poutres de soutien et des profilés PZ/PZC

**Caractéristiques**

Nuances d'acier:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Poids PBS-M:	~13,4 kg/m
Poids PBS-F:	~15,9 kg/m

**PBS-M / PBS-F****Kombiwandprofile**

Für PZ und PZC (Ball and Socket)

**Einsatzgebiet**

Erstellen von Kombiwänden mit Keulenträgern und PZ/PZC-Profilen

**Eigenschaften**

Stahlgüten:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Gewicht PBS-M:	~13,4 kg/m
Gewicht PBS-F:	~15,9 kg/m

**PBS-M / PBS-F****Profilo parete combinata**

Per PZ e PZC (maschio e femmina)

**Campo di applicazione**

Realizzazione di pareti combinate con travi a doppia T e profili PZ/PZC

**Caratteristiche**

Qualità dell'acciaio:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso PBS-M:	~13,4 kg/m
Peso PBS-F:	~15,9 kg/m

**PBS-M / PBS-F****Perfiles de pantalla combinada**

Para PZ y PZC (Ball and Socket)

**Ámbito de aplicaciones**

Formación de pantallas combinadas con portamazas y perfiles PZ/PZC

**Propiedades**


Calidades de acero:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso PBS-M:	~13,4 kg/m
Peso PBS-F:	~15,9 kg/m

# PBS-M / PBS-F

# for Ball & Socket (PZ / PZC)



PBS-M



PBS-F

